

Quadruple Tourbillon Black Limited edition of 8 pieces in black ADLC titanium Hand-wound movement with patented tourbillon

Quadruple Tourbillon • hours and minutes • small seconds • 4-minutes outer-tourbillons rotation • power-reserve

Movement

Movement dimensions

- Diameter: 36.40 mm
- Thickness: 9.70 mm

Number of parts

- Movement: 534 parts
- 4 tourbillon cages: 261 parts
- . Total weight of the cages: 2.26 g
- Spherical differential: 28 parts

Number of jewels

- 63
- · Olived-domed jewels in gold chatons

Chronometric power reserve

• 50 hours

Barrels

 Two series-coupled fast rotating barrels (1 turn in 3.2 hours), one of which is equipped with a slipping spring to avoid excess tension

Balance wheel

 Variable-inertia with white gold mean-time screws (10.70 mm diameter)

Frequency

· 21'600 vibrations/hour

Balance spring

- · Phillips terminal curve
- Geneva-style stud

Main plates

 Nickel silver, spotted with polished bevelling and countersinks, straight-grained flanks, nickel-palladium treatment

Bridges

- Nickel silver, frosted and spotted with polished bevelling and countersinks, straight-grained flanks, nickel-palladium treatment
- Gold plate engraved with the individual number
 Two steel tourbillon bridges (movement side) :
- Two steel tourbillon bridges (movement side): flat black polished with hand-polished bevelling and countersinks
- Two synthetic sapphire tourbillon bridges (dial side)

Inner tourbillons

Inclined at a 30° angle, 1 rotation per minute

Outer tourbillons

- 1 rotation in 4 minutes
- Hand-bevelled and openworked cage pillars
- 1 gold counterweight per double cage bearing the individual number of the timepiece

Gearing

- Involute circle profile
- Conical gearing with profiled teeth

Displays

- Hours and minutes
- Small seconds on a sector (mean performance)
- 50-hours power reserve on a sector
- 240-seconds outer-tourbillon rotation (on one of the outer cages)

Exterior

Case

- In black ADLC titanium with asymmetrical convex synthetic sapphire crystal
- Transparent back with asymmetrical convex synthetic sapphire crystal
- Lateral window with shaped synthetic sapphire crystal
- Three-dimensional, variable geometry-shaped lugs
 Raised polished engraving "Quadruple" and
- "Greubel Forsey" on a hand-punched background
- Gold security screws
- Polished bezel, caseband with hand-finished straight graining
- Engraved individual number

Case dimensions

- Diameter: 43.50 mm
- Height: 16.11 mm

Water resistance of the case

 Water-resistant 3 atm - 30 m - 100 ft (standard NIHS 92-20/SN ISO 22810:2010)

Crown

• In black ADLC titanium with engraved and GF logo

Dial

- · Multi-level in gold, black colour
- Gold hour markers
- · Gold display sectors
- Gold GF logo

Hands

- Hours and minutes in polished gold,
- with Super-LumiNova
- Small seconds, 240-seconds and power-reserve in polished gold

Strap and clasp

- Black rubber or hand-sewn alligator
- Black ADLC titanium folding clasp, engraved with the GF logo